

使用前请仔细阅读本说明书，并妥善保管。

**注意事项**

- 不要让设备与硬物摩擦，否则可能会导致设备表面磨花或其他硬件损坏。
- 请使用本设备指定的电压 (DC 12V/24V)，否则可能造成设备工作异常或损坏。
- 长时间不使用，请将设备脱离电源。
- 如果设备进水或粘有尘土等污物，请勿使用。
- 请勿将设备暴露在热源、明火附近或超过60°C的环境中。
- 请将设备存放在阴凉处避免阳光直射。
- 请勿使设备短路。
- 非专业人员请勿擅自拆开维修。

**包装清单**

- 70迈金属双口车充 × 1
- 说明书 (内含三包凭证) × 1

01

**产品介绍**




02

**产品参数**

型号: Midrive CC02  
 输入: 12V / 24V 直流  
 输出(黑色): 5V 3A, 9V 2A, 12V 1.5A  
 输出(橙色): 5V 3A, 9V 2A, 12V 1.5A  
 输出接口: 双USB接口  
 工作温度: 0°C ~ 30°C  
 存储温度: -30°C ~ 80°C

**产品使用**

本产品支持QC3.0快充。拔出或者打开车辆点烟器的盖子，确保点烟器内部干净无异物。将车充头插入点烟器中，通电后指示灯白色常亮。70迈金属双口车充有智能温度保护功能。当温度过高时，车充会自动停止充电。当温度回落到正常后，车充会恢复给电子设备充电。

03

**产品中有害物质的名称及含量**

部件名称	有害物质				
	铅 (Pb)	汞 (Hg)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
主机外壳及组件	X	○	○	○	○
主机内部电子组件	○	○	○	○	○

本表格依据SJ/T 11364的规定编制。  
 ○表示该有害物质在该部件所有均质材料中的含量均在GB/T26572规定的限量要求以下。  
 X表示该有害物质至少在该部件的某一均质材料中的含量超出了GB/T26572规定的限量要求。

04

**联系我们**

官网: www.70mai.com  
 电话: 400-015-2599  
 制造商: 上海新豪数字科技有限公司  
 地址: 上海市闵行区象星路588号2幢2220室  
 扫描右侧二维码关注70迈微信公众号





Read this manual carefully before use, and retain it for future reference

**Precautions**

- To prevent surface scratches and other hardware damages, please do not allow the product to rub against other solid objects.
- To prevent product malfunction and damage, please use the specified voltage (12V/24V).
- When the product is not in use for an extended period of time, please do not leave it plugged into the cigarette lighter.
- Please do not use the product after it comes in contact with water, or if it is covered with dust or dirt.
- If you are not a professionally trained technician, please do not attempt to disassemble or repair the product on your own.
- Do not expose the product to heat sources, open fire or environments where the ambient temperature is over 60°C (140°F).
- Do not store in direct sunlight.
- Do not short circuit the product.

05

**Product Overview**

06

**Specifications**

Model: Midrive CC02  
 Input: 12V / 24V 直流  
 Output (Black): 5V 3A, 9V 2A, 12V 1.5A  
 Output (Orange): 5V 3A, 9V 2A, 12V 1.5A  
 Output Port: Dual USB Ports  
 Operating Temperature: 0°C ~ 30°C  
 Storage Temperature: -30°C ~ 80°C

**Package Contents**

- 70mai Dual USB Car Charger × 1
- User Manual × 1


**How to Use**

The product supports QC3.0 quick charge. Remove or open the cover of the cigarette lighter receptacle, make sure the inside is clean and free of foreign objects, then plug the car charger into the cigarette lighter receptacle. The indicator light is solid white while your device is charging.

07

70mai Dual USB Car Charger has an intelligent temperature control function. When the temperature is too high, it will automatically interrupt power output. After the temperature has dropped to a safe range, it will resume charging the electronic device.

**Caution:**  
 This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



Service: help@70mai.com  
 For further information, please go to www.70mai.com  
 Manufactured by: 70mai Co., Ltd.  
 Address: Room 2220, Building 2, No. 588 Zixing Street, Minhang District, Shanghai, China

08

70迈金属双口车充使用说明书  
 70mai Dual USB Car Charger User Manual

